



R70

Flexibility for any application

Characteristics

- Multiband Radio with Full-Duplex communication
- Highly field-customizable
- External EEPROM SIM module
- Frequencies management against interferences
- STOP: PLd, Category 3 according to EN ISO 13849-1:2008
- Easy and fast maintenance
- Multi-feedback capability
- 29 digital and 8 analogue outputs
- Suitable for all common proportional valves

Specifications

Receiver	R70
Stop Function	Cat. 3 - PLd
Ingress protection	IP65/NEMA4
Frequency Band	Multiband (400 - 930 MHz)
AC Power Supply	48/115/230 Vac
DC Power Supply	9 -35 Vdc
Antenna	Internal / External
Removable EEPROM	Internal
Signalling	Internal
ON/OFF outputs (Max.)	29
Analogue Outputs (Max.)	8
CANOpen, Profibus-DP, SAE J1939	YES
ON/OFF inputs (Max.)	44
Analogue Inputs (Max.)	8
Maximum output Current	8A
Working Temperature Range	-20C +70C (-4F +158F)
Weight (gr)	Config dependable
Dimensions (LxWxH mm)	285x200x110
Cable connection	YES
Associated Transmitters	T70/1, T70/2, T70/1 HALL, T70/2 HALL, T70/1 ATEX, T70/2 ATEX, IK2, IK3, IK4



HEADQUARTERS

IKUSI - Ángel Iglesias S.A. · Pº Miramón, 170 · 20014 San Sebastián · SPAIN
Tel.: +34 943 44 88 00 · Fax: +34 943 44 88 20 · tlc@ikusi.com · www.ikusitlc.com

IKUSI WORLDWIDE

AUSTRALIA/NEW ZEALAND · BRAZIL · CHILE · COLOMBIA · FRANCE · GERMANY · INDIA · MEXICO · SPAIN · UNITED ARAB EMIRATES



Leading Brands of Spain Forum